

**Bases tripolares verticales abiertas, 185 mm distancia de embarrado**  
**3 Pole vertical design fuse rails, 185 mm busbar spacing**  
**(BTVA/BTVA-P)**

**A** 250|400|630

Gama / Range

Referencia Reference	Tipo Type	Intensidad Current	Protección Protection	Conexión Connections	Fusible Fuse-link	Distancia de embarrado Busbar spacing
415.11.10.XX.YY	BTVA	250 A		Superior / Inferior reversible Top / Bottom reversible	NH 1	185 mm
415.12.10.XX.YY	BTVA	400 A	Sin protección Without protection	Superior / Inferior reversible Top / Bottom reversible	NH 2	185 mm
415.13.10.XX.YY	BTVA	630 A		Superior / Inferior reversible Top / Bottom reversible	NH 3	185 mm
415.21.10.XX.02	BTVA-P	250 A	Protegida 100 mm 100 mm protection	Superior / Inferior reversible Top / Bottom reversible	NH 1	185 mm
415.22.10.XX.02	BTVA-P	400 A		Superior / Inferior reversible Top / Bottom reversible	NH 2	185 mm
415.23.10.XX.02	BTVA-P	630 A		Superior / Inferior reversible Top / Bottom reversible	NH 3	185 mm
415.31.10.XX.02	BTVA-P	250 A		Superior / Inferior reversible Top / Bottom reversible	NH 1	185 mm
415.32.10.XX.02	BTVA-P	400 A	Protegida 120 mm 120 mm protection	Superior / Inferior reversible Top / Bottom reversible	NH 2	185 mm
415.33.10.XX.02	BTVA-P	630 A		Superior / Inferior reversible Top / Bottom reversible	NH 3	185 mm

